

EU-Material-safety-data-sheet

Trade-Name: Solder Wire HS10 Sn60Pb38Cu2

Product no.:

Date of issue:5.12.2002

page: 1(2)

1. Chemical Identification

Trade-name: **Solder Wire HS10 Sn60Pb38Cu2**

Manufacturer: Stannol GmbH
Oskarstr.3-7
42283 Wuppertal
Phone.: 0202 / 5850 2.Phone:-0202 / 585119

Phone: 0202 / 585118

2. Composition/Information of Ingredients

Chemical characteristic: Tin/Lead/Copper-alloy with flux max. 3,5 % rosin, halide-activated

Ingredients:

Proportion	CAS-No.	Symbols	Risk-Phrases	Chemical name
59,5-60,5%	7440-31-5			Tin
>36%	7439-92-1			Lead
1,5-2,0%	7440-50-8			Copper
<3,5%	8050-09-7	Xi	43	Rosin

3. Hazards Identification:

Not a composition for the purposes of the Dangerous Substances Regulations, but nevertheless observe items 4-16

4. First Aid Measures:

Inhalation: Apply fresh air(soldering vapours)
In case of contact with skin:: In use of contact, wash with water and soap
Eye contact: Summon doctor
Ingestion: Summon doctor

5. Fire Fighting Measures

Extinguishing Media: Use extinguishing media appropriate to surrounding fire conditions
Special Fire-fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

6. Accidental Release Measures:

Pick up and place in appropriate container

7. Handling and Storage:

The fumes(soldering vapours) should be extracted away from the breathing zone of the operators. Ensure the area is well ventilated. Wash hands with soap and warm water after handling, particularly before eating, drinking or smoking.

EU-Material-safety-data-sheet

Trade-Name: Solder Wire HS10 Sn60Pb38Cu2

Product no.:

Date of issue:5.12.2002

page: 2(2)

8. Exposure Controls / Personal Protection:

Local exhaust or dilution ventilation and control of process conditions are suitable methods..

Substance	CAS-No	ml/m ³ (ppm)	mg/m ³	Art
Tin	7440-31-5		2	MAK (NL)
Lead	7439-92-1		0,1	MAK (TLV)
Copper	7440-50-8		1	MAK (DFG)

BAT-Value	Lead/blood level:	700µg/l,
	Women below 45 years:	300µg/l

Respiratory Protection: If concentrations are over the exposure limit, use a supplied air respirator.

Hand Protection: Use heat resistant gloves if required.

Eye Protection: Operators should wear goggles

9. Physical and Chemical Properties

Appearance and Odour:	Solid and odourless
Color:	grey
Melting Point:	>183 °C
Boiling point of lead:	1735°C
Vapour Pressure:	n.d. Lead at 328°C
Density(20°C):	8,2-9,3 g/cm ³

10. Stability and Reactivity:

Dangerous reactions:	Possible with oxidising agents.
Hazardous combustion or decomposition products:	Lead-oxides possible

11. Toxicological Information

Acute Effects:

Acute intoxication by ingestion of skin contact with lead is improbable. High doses nevertheless lead to symptoms of poisoning..

Contamination through skin contact and inhalation: Rosin is a sensitizer

Inhalation of rosin fumes can irritate the respiratory tract and eyes. The formation of lead in fumes is negligible at soldering temperatures.

Toxicity Data (of Lead):

LD.L0	160	oral	pigeon
LD.L0	1000	ip	rat

12. Ecological Information:

Lead and combinations of lead are not biological reducible.

13. Disposal Considerations:

Contact a licensed professional waste disposal service to dispose of this material.
Observe all federal, state and local environmental regulations. Collect metal for recycling

14. Transport Information:

GGVS/ADR/RID: The product is not classified as hazardous for transport

15. Regulatory Information:

German regulations:

TRGS:	505 Lead
TRGS:	900 MAK
TA-Air:	KL III

Not subject to current legislation

EU-Material-safety-data-sheet

Trade-Name: Solder Wire HS10 Sn60Pb38Cu2

Product no.:

Date of issue:5.12.2002

page: 3(2)

16. Other Information:

Other information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide..

Safety data-sheet is written by:

Save of quality/laboratory

Contact-person:

Dr. W. Kruppa